

Gekatex S.A.S. Technical Textiles and Surface Treatment Systems for O.E.M.

TECHNISCHE FICHE / TECHNISCHES DATENBLATT / TECHNICAL DATA SHEET / FICHE TECHNIQUE

Wet Line - GEKACLEAN
(100% PP Polypropylen)
Thermobonded Material
Sealant and Adhesive Removal Wet Wiper

Material Description

Presat Non Woven sealant and adhesive removal wipes in a bucket
Removes bitumous residues, adhesives and oversprays from car body
Gekaclean replaces Heptane and its Neutral pH value protects workers skin and the environment. It's soft resistant basesheet is designed to respond to the needs of the OEM and after market transport segment usage.

Physical Properties

Tests	Orientation	Units	Targets	Methods
Basis weight		g/M ²	30	ISO9073-3
Thickness		mm	0,2	ISO9073-2
Tensile strength	MD	N dry/wet	20	ISO9073-3
	CD	N dry/wet	18	ISO9073-3
Elongation at break	MD	% dry / wet	13	ISO9073-3
	CD	% dry / wet	40	ISO9073-3

Functions

Tests	Units	Targets	Methods
Absorption Capacity	%	450	EN1644-1

Properties of finished product

Description	Data
Packaging Units	Dispenser Bucket
Number of sheets	150 V-Folded
Sheet Length	275 mm
Sheet Width	275 mm
Roll diameter	165 mm
Baseweight	30 g/m ²
Waterabsorption	135 g/m ²
Absorption Speed	< 2 sec
Embossing	small waffle calender